=> d his

L4

L9

L13

L16

```
(FILE 'HOME' ENTERED AT 08:28:04 ON 22 AUG 2007)
```

FILE 'HCAPLUS' ENTERED AT 08:28:18 ON 22 AUG 2007

E SHUNICHI MATSUO/AU 25

E MATSUO SHUNICHI/AU 25

L1 12 S (E3)

E TAKAMURA TAKATSUGU/AU 25

L2 2 S (E3)

E MATSUO SHUNICHI/IN 25

L3 12 S (E3)

E TAKAMURA TAKATSUGU/IN 25

יים (בכי) די אוריים

2 S (E3)

L5 13 S L1-L4 L6 13 DUP REM

13 DUP REM L5 (0 DUPLICATES REMOVED)

L7 2 S L5 AND ?CELLULOSE?

FILE 'STNGUIDE' ENTERED AT 08:30:52 ON 22 AUG 2007

FILE 'HCAPLUS' ENTERED AT 08:43:46 ON 22 AUG 2007

L8 42038 S CELLULOSE ACETATE

13221 S BAGASSE OR KENAF OR REEDS OR RICE STRAW

L10 53 S L9 AND L8

L11 42 S L10 AND 1800<=PY<=2003

L12 0 S L11 AND PRESSURE AND STEAM

6 S L11 AND PRESSURE

L14 0 S L11 AND STEAM

FILE 'STNGUIDE' ENTERED AT 08:46:24 ON 22 AUG 2007

FILE 'HCAPLUS' ENTERED AT 08:46:58 ON 22 AUG 2007

E ACETIC ANHYDRIDE+ALL/CT

L15 155478 S (ACETIC ANHYDRIDE OR "CHEMICAL COMPOUNDS" OR "ORGANIC COMPOUN

4 S L15 AND L11

L17 3 S L16 NOT L13

FILE 'STNGUIDE' ENTERED AT 08:47:44 ON 22 AUG 2007

FILE 'STNGUIDE' ENTERED AT 09:02:40 ON 22 AUG 2007

L17 ANSWER 1 OF 3 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1995:126702 HCAPLUS

DOCUMENT NUMBER: 122:293668

TITLE: Acetylation of high α -cellulose pulp extracted

from fast growing plant species

AUTHOR(S): Saikia, C. N.; Dass, N. N.; Baruah, J. N. CORPORATE SOURCE: Regional Res. Lab., Jorhat, 785 006, India SOURCE: Cellulose Chemistry and Technology (1994),

28(1), 21-7

CODEN: CECTAH; ISSN: 0576-9787

DOCUMENT TYPE: Journal LANGUAGE: English

AB High α-cellulose (I) pulp was extracted from Leucaena glauca, a fast-growing perennial plant, and kenaf, an annual plant, and acetylated products were prepared from I following a homogeneous acetylation procedure, using acetic anhydride. An acetylated product was also prepared from a com. available I pulp, under identical conditions. IR, 1H-NMR, and 13C-NMR studies were done to characterize the acetylated products. The properties of acetylated products obtained from I from the 2 fast growing plant species were very much similar to the product obtained from com. available I pulp.

L17 ANSWER 2 OF 3 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1994:57012 HCAPLUS

DOCUMENT NUMBER: 120:57012

TITLE: Manufacture of cellulose esters and filled plastics

from wastepaper and bagasse

INVENTOR(S): Elion, Glenn R.

PATENT ASSIGNEE(S): International Communications and Energy, USA

SOURCE: U.S., 9 pp. CODEN: USXXAM

DOCUMENT TYPE: Patent LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND DATE	APPLICATION NO.	DATE
US 5244945	A 19930914	US 1992-916659	19920720 <
WO 9402539	A1 19940203	WO 1993-US6429	19930708 <
W: AT, AU, BB,	BG, BR, BY, CA, C	CH, CZ, DE, DK, ES, FI	, GB, HU, JP,
KP, KR, KZ,	LK, LU, MG, MN, M	MW, NL, NO, NZ, PL, PT	RO, RU, SD,
SE, SK, UA,			
		BB, GR, IE, IT, LU, MC	
		GN, ML, MR, NE, SN, TD	, TG
AU 9346686	A 19940214	AU 1993-46686	19930708 <
PRIORITY APPLN. INFO.:		US 1992-916659	A 19920720
		WO 1993-US6429	W 19930708 ·

AB Cellulose esters and filled plastics are manufactured by reacting waste paper or bagasse with an acid anhydride in the presence of a catalyst, recovering the cellulose ester from the reaction mixture, and, when necessary, separating ink from the cellulose ester by filtration or solvent extraction

L17 ANSWER 3 OF 3 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1992:176324 HCAPLUS

DOCUMENT NUMBER: 116:176324

TITLE: Homogeneous esterification of high α -cellulose

extracted from Leucaena leucocephala and Hibiscus

cannabinus

AUTHOR(S): Saikia, C. N.; Baruah, J. N.; Dass, N. N. CORPORATE SOURCE: Reg. Res. Lab., Jorhat, 785 006, India

SOURCE:

Indian Journal of Fibre & Textile Research (

1991), 16(3), 213-17 CODEN: IJFRET; ISSN: 0971-0426

DOCUMENT TYPE: LANGUAGE:

Journal English

High α -cellulose pulp was extracted from two fast growing plants, Leucaena leucocephala (a perennial plant) and Hibiscus cannabinus (an annual plant), and then esterified with mono- and tri-carboxylic acid anhydrides following a homogeneous esterification procedure. The physico-chemical properties of the esterified products were studied and the products were characterized using IR and PMR techniques. The esterified products from the α -cellulose of above plants showed properties similar to those of esters prepared from com. available rayon-grade pulp.

L13 ANSWER 1 OF 6 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 2000:422140 HCAPLUS

DOCUMENT NUMBER: 133:136932

TITLE: An efficient, one-pot acylation of cellulose under

homogeneous reaction conditions

AUTHOR(S): El Seoud, Omar A.; Marson, Guilherme A.; Ciacco,

Gabriela T.; Frollini, Elisabete

CORPORATE SOURCE: Instituto de Quimica - Universidade de Sao Paulo, Sao

Paulo, 05513-970, Brazil

SOURCE: Macromolecular Chemistry and Physics (2000),

201(8), 882-889

CODEN: MCHPES; ISSN: 1022-1352

PUBLISHER: Wiley-VCH Verlag GmbH

DOCUMENT TYPE: Journal LANGUAGE: English

Cellulose (I) samples from cotton linters, sisal, and sugarcane AB bagasse were successively acylated (acetate, propionate, butyrate, and acetate/butyrate) under homogeneous reaction conditions, in LiCl/N, N-dimethylacetamide (DMAC), by the following procedure: (1) I and LiCl are heated under decreased pressure, at 110°; (2) I is dissolved in LiCl/DMAC by heating at 155°, followed by cooling to 40°; (3) the solubilized polymer is acylated at 60° for 18 h. Attractive features of this 1-pot procedure include: easy control and high reproducibility of the degree of substitution; elimination of base catalyst; negligible degradation of the natural polymer; and recovery/recycling of high purity DMAC and acid anhydride. Reaction conditions employed for the present I samples are different from those previously used for Avicel PH 101 microcryst. I because their fibrous nature, higher indexes of crystallinity, and higher mol. wts. retard their dissoln. and decrease their rates of acylation by acid anhydrides.

REFERENCE COUNT: 47 THERE ARE 47 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L13 ANSWER 2 OF 6 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1955:55188 HCAPLUS

DOCUMENT NUMBER: 49:55188
ORIGINAL REFERENCE NO.: 49:10625d-e

TITLE: High-purity cellulose

INVENTOR(S): Asensio, Constantino Casanovas

DOCUMENT TYPE: Patent LANGUAGE: Unavailable

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO. KIND DATE APPLICATION NO. DATE

ES 213734 19540503 ES

Pure cellulose, which is suitable for being transformed into the xanthogenate or the acetate, is obtained from very cheap raw materials, such as esparto grass, sugar cane bagasse, and cereal husks, by first washing these materials with a hot or cold acid or alkaline solution with or without pressure. Then the material is treated with 0.05-10% HNO3 from 10 min. to 5 hr. at 20-180°. This treatment serves to remove the mannans and xylans which cause a discoloration. The material is then bleached with Ca(ClO)2, NaClO2, Cl, ClO2, NaOCl, or any other suitable bleaching agent and washed with cold or warm water or dilute alkaline Finally, in order to reduce the ash content, the material is washed with mineral acids. After this washing, or after the bleaching operation, the material must be treated with SO2 if Fe is present.

L13 ANSWER 3 OF 6 HCAPLUS COPYRIGHT 2007 ACS ON STN ACCESSION NUMBER: 1945:1078 HCAPLUS

22/08/2007

DOCUMENT NUMBER: 39:1078
ORIGINAL REFERENCE NO.: 39:172g-i

TITLE: Thermoplastically bonded fibrous material

INVENTOR(S): Levey, Constance D.

DOCUMENT TYPE: Patent LANGUAGE: Unavailable

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

KIND DATE APPLICATION NO. DATE PATENT NO. US 2347697 19440502 19440502 US 1939-307275 19391202 <--AΒ Fibers, such as wastes from saw mills, sugar-cane refineries or flour mills, are shredded to a desired length, preferably less than 1/2 in., and mixed with powdered gilsonite, rosin, asphalt, pitch and the like, forming about 1/4 of the mixture The fibers are preferably predried to approx. 10% moisture, before the mixture is molded under pressure of about 200-400 lb. per sq. in. at temps. 150-250°F. Powdered bagasse may be used instead of fibrous material and on one or both platens of the molding machine is placed a layer of thermoplastic material, such as cellulose acetate, ethylcellulose, polystyrene or urea-HCHO. The laminated board thus formed of the desired thickness may be dyed or pigmented, and is made impervious to pests by addns. of small amts. of insecticides to gilsonite, rosin, asphalt or whatever binder is hardness.

L13 ANSWER 4 OF 6 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1938:62577 HCAPLUS DOCUMENT NUMBER: 32:62577

DOCUMENT NUMBER: 32:62577
ORIGINAL REFERENCE NO.: 32:8774c-e

TITLE: Utilization of rice straw

AUTHOR(S): Lopez, Daniel R.; Robinson-Gomez, Lilly

SOURCE: Univ. Philippines Nat. and Applied Sci. Bull. (

1938), 6, 103-7

DOCUMENT TYPE: Journal LANGUAGE: Unavailable

AB Rice straw (100 g.) was cooked for 12-14 hrs. at 15 lb. pressure with a solution of 150 g. Na2CO3, 150 g. Na2SO4, 75 g. NaHSO3 and 9 g. ZnSO4. The resulting pulp was boiled with alkali, bleached, acidified with 0.5% HCl solution, washed and air-dried. The air-dry cellulose yield was 27.87% and the final product contained 5.02% H2O, 1.41% ash, 78.43% α -cellulose and it had a Cu number of 1.15. Cellulose acetate was prepared from this pulp. The utilization of this pulp for paper and cellulose derivs. is discussed briefly.

L13 ANSWER 5 OF 6 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1931:44455 HCAPLUS

DOCUMENT NUMBER: 25:44455 ORIGINAL REFERENCE NO.: 25:5026i

TITLE: Fiber from bagasse or the like

INVENTOR(S): Richter, George A.

PATENT ASSIGNEE(S): Brown Co.
DOCUMENT TYPE: Patent
LANGUAGE: Unavailable

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO. KIND DATE APPLICATION NO. DATE

US 1811864 19310630 US 1927-162417 19270120 <--

AB The material is steeped at about room temperature in an alkaline liquor of an alkalinity

at least equivalent to 7% NaOH until the liquor has thoroughly diffused and penetrated into the material, followed by cooking at atmospheric pressure in the liquor.

L13 ANSWER 6 OF 6 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1931:17936 HCAPLUS

DOCUMENT NUMBER: 25:17936
ORIGINAL REFERENCE NO.: 25:1993c-d

TITLE: Molded products from cellulosic material

INVENTOR(S): Smyser, Frederic H.
PATENT ASSIGNEE(S): General Electric Co.

DOCUMENT TYPE: Patent LANGUAGE: Unavailable

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO. KIND DATE APPLICATION NO. DATE
-----US 1792254 19310210 US 1929-401627 19291022 <--

AB A cellulosic material such as sawdust, bagasse or cornstalks having natural substances capable of yielding resinous compds. is digested with NaOH, and H2SO4 is added to the digested mass to precipitate the dissolved resinous constituents, the material is filtered and the mass is washed until neutral, dried at about 80° and there is added to the dried mass about 5-40% of hydrated lime, the material is powdered and is molded under heat and pressure.

22/08/2007

INVENTOR(S):

=> d 17 ibib abs 1-2

ANSWER 1 OF 2 HCAPLUS COPYRIGHT 2007 ACS on STN L7

ACCESSION NUMBER: 2004:794575 HCAPLUS

DOCUMENT NUMBER: 141:297538

TITLE: Process for manufacturing cellulose molding,

plant component extracting apparatus, and process for

producing cellulose acetate Matsuo, Shunichi; Takamura,

Takatsugu

PATENT ASSIGNEE(S): Nihon Zaikei Kabushiki Kaisha, Japan

SOURCE: Eur. Pat. Appl., 32 pp.

CODEN: EPXXDW

DOCUMENT TYPE: Patent LANGUAGE: English

FAMILY ACC. NUM. COUNT:

PATENT INFORMATION:

PATENT NO.		DATE .	APPLICATION NO.	DATE	
			EP 2004-251357		
R: AT, BE, CH,	DE, DK	, ES, FR,	GB, GR, IT, LI, LU, N	L, SE, MC, PT,	
			CY, AL, TR, BG, CZ, E		R
JP 2004285306	A	20041014	JP 2003-82508	20030325	
JP 2004299247	Α	20041028	.JP 2003-82508 JP 2003-94721	20030331	
SG 129268	A1	20070226	SG 2003-7738	20031229	
IN 2004KO00091	Α	20060303	SG 2003-7738 IN 2004-KO91	20040304	
US 2004241302	A1	20041202			
CN 1532208	Α	20040929	CN 2004-10008917	20040315	
AU 2004201074		20041014	AU 2004-201074	20040315	
CN 1789285		20060621	AU 2004-201074 CN 2005-10127455	20040315	
CN 1803847		20060719			
JP 2004306021					
CA 2461621			CA 2004-2461621		
KR 2004084754	Α	20041006		20040324	
BR 2004000773		20050111		20040325	
KR 2005109272		20051117	KR 2005-102183	20051028	
KR 2006004881		20060116	KR 2005-109682	20051116	
AU 2005239677		20051222			
AU 2005239683		20051222			
PRIORITY APPLN. INFO.:			JP 2003-82508	A 20030325	
			JP 2003-82509		
			JP 2003-94721	A 20030333	
			AU 2004-201074		
			CN 2004-10008917		
			KR 2004-19908		
			KR 2005-102183		
AB A process for manuf	acturin	g a cellu	lose molding, comprise		

A process for manufacturing a cellulose molding, comprises: steaming corncob meal at a temperature of 150 to 250° and a pressure of 20 to 29 MPa; filtering the steamed corncob meal with a filtering device to obtain a solid; and molding the solid;. The molding step comprises: separating the solid into a first solid and a second solid; dehydrating and acetylating the first solid by adding acetic anhydride and sulfuric acid thereto; filtering the dehydrated and acetylated solid with a filtering device to remove a solid and obtain filtrate; and stirring and mixing the filtrate and the second solid to obtain a liquid product. The plant component extracting apparatus comprises: raw material processing means including a raw material supply portion for supplying a plant raw material and a raw material pressurizing portion for heating and pressurizing the supplied plant raw material at 150 to 350° and 5 to 30 MPa, resp.; hot water supply means including a pressurizer (P1) and a heater and supplying sub-critical water having a temperature of 300 to 350° pressurized at a pressure of 28 to 30 MPa; and hot water reacting means for carrying out a steaming

treatment by mixing the heated and pressurized plant raw material with the sub-critical water supplied from the hot water supply means;. A process for manufacturing cellulose acetate comprises: steaming a material selected from bagasse, kenaf, reeds and rice straw in a pressure vessel at a temperature of 150 to 350° and a pressure of 15 to 29 MPa; filtering the steamed material with a filtering device to obtain a solid; and dehydrating and acetylating the solid by adding acetic anhydride and sulfuric acid to the solid.

L7 ANSWER 2 OF 2 HCAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER:

2003:357414 HCAPLUS

DOCUMENT NUMBER:

138:339877

TITLE:

Manufacture of cellulose acetate from

corncob wastes for biodegradable plastics in reduced steps by cooking milled corncob in a pressure vessel

at 150-250°, filtering the materials and dehydroacetylating cellulose by adding

acetic anhydride and sulfuric acid to the filtered

solid materials

INVENTOR(S):

Matsuo, Shunichi; Takamura, Koji

PATENT ASSIGNEE(S): SOURCE:

Nihon Zaidan K. K., Japan Jpn. Tokkyo Koho, 5 pp.

CODEN: JTXXFF

DOCUMENT TYPE:

Patent Japanese

LANGUAGE:

Japanese

FAMILY ACC. NUM. COUNT:

PATENT INFORMATION:

	PAT	TENT	NO.			KINI) DI	TE	AP	PLICAT					ATE	
	JP	3405	981			В1	20	030512		2002-						
	JP	2004	0270	56		Α	20	040129								
	JP	2004	0242	34		Α	20	040129	JP	2002-	3641	12		2	0020	626
	JP	3522	264			B2	20	040426								
	CA	2429	079			A1	20	031226	CA	2003-	2429	079		2	0030	516
	CA	2429	1079			C	20	061114								
	US	2004	0025	98		A1	20	040101	US	2003-	4398	09		2	0030	516
	US	6984	731			B2	20	060110								
	ΕP	1375	522			A2	20	040102	EP	2003-	1134	0		2	0030	519
	EР	1375	522			A 3	20	040107								
								061122								
		R:							GB, G							
			ΙE,	SI,	LT,	LV,	FI, F	O, MK,	CY, A	L, TR,	BG,	CZ,	EE,	HU,	SK	
	KR	2004	0025	12		Α	20	040107	KR	2003-	3155	0		2	0030	519
	ΑU	2003	2042	73		A1	20	040115	AU	2003-	2042	73		2	0030	519
	ΕP	1466	926			A2	20	041013	EP	2004-	1448	0		2	0030	519
								050316								
		R:	ΑT,	BE,	CH,	DE,	DK, E	S, FR,	GB, GI	R, IT,	LI,	LU,	NL,	SE,	MC,	PT,
			IE,	SI,	LT,	LV,	FI, F	O, MK,	CY, A	L, TR,	BG,	CZ,	EE,	HU.	SK	
	AT	3460	97			${f T}$	20	061215	AT CN BR	2003-	1134	0		2	0030	519
	CN	1467	225			Α	20	040114	CN	2003-	1313	97		2	0030	520
	BR	2003	0020	01		Α	20	040824	BR	2003-	2001			2	0030	520
	MX	2003	PA04	491		Α	20	050203	MX	2003-	PA44	91		2	0030.	520
	IN	1953	81			A1	20	050211	IN	2003-	CA28	1		2	0030	520
	HK	1060	580			A1	20	070404	HK	2004-	1025	22		2	0040	408
	ΑU	2004	2053	23		A1	20	041007	AU	2004-	2053	23		2	0040	830
	IN	2004	KO00	541		Α	20	060203	IN	2004-	KO54	1		2	0040	908
PRIOR	YTI S	APP	LN.	INFO	. :				JP	2002-	1864	76	1	13 2	0020	626
									AU	2003-	2042	73	7	A3 2	0030	519
									EP	2003 - 2003 -	1134	0	I	A3 2	0030	519
									IN	2003-	KO28	1	I	A3 2	0030	520

AB Cellulose acetate (I) is prepared by the steps comprising the steps of (a) cooking milled corncob in an autoclave at 150-250° and

20-29 MPa, (b) filtering the materials, and (c) dehydroacetylating cellulose by adding acetic anhydride (II) and H2SO4 to the filtered solid materials. A mixture containing milled corncob 100, CaSO3 5, and H2O 50 parts was kneaded in a sealed extruder for 5 min at 100° and 3.5 Mpa, subsequently kneaded in a sealed extruder at for 5 min at 150° and 10 MPa, subsequently kneaded in a sealed extruder for 5 min at 200° and 22 MPa, finally kneaded in a sealed extruder for 15 min at 220° and 28 MPa, and filtered to give solid materials. The solid materials were stirred in a mixture of AcOH 5, II 10, and H2SO4 5 parts per 100 parts solid material for 24 h at 10 MPa and 60 rpm to give I with sp. gr. 1.33 (at 25°) and 1.36 (at 4°), bulk d. 0.25-0.5 kg/L, glass transition temperature 160-180°, and m.p. 230-300°.

=> fil stng
COST IN U.S. DOLLARS

SINCE FILE TOTAL

Searched fo	or:: :All of the words:(((kenaf OR bagasse OR reeds OR rice) AND extru* AND pressure) AND (I
Four	nd:: :294 total 7 journal results 258 preferred web results 29 other web results
Sort b	y:: :relevance date
	Save checked results Email checked results Export checked results
	A bioethanol process development unit: initial operating experiences and results with a corn fiber feedstock Schell, D.J. / Riley, C.J. / Dowe, N. / Farmer, J. / Ibsen, K.N. / Ruth, M.F. / Toon, S.T. / Lumpkin, R.E. , Bioresource Technology, 91 (2), p.179-188, Jan 2004
·	opportunities with low cost feedstocks such as bagasse (BCI) and municipal solid waste (Masadabiomass mixer a high-temperature, high- pressure reactor system and a flash tank. Thedischarge port. The reactor is heated by steam to achieve the desired temperature andconditions Temperature (^oC) 30 30 30 30 30 30 30 Pressure (kPa) - b b (-) not applicable 133
	Published journal article available from ScienceDirect
	view all 6 results from ScienceDirect similar results
<u> </u>	Potential and utilization of thermophiles and thermostable enzymes in biorefining Turner, Pernilla / Mamo, Gashaw / Karlsson, Eva Nordberg , Microbial Cell Factories, 6, p.9-9, Mar 2007 doi:10.1186/1475-2859-6-9desired activities, for development of better thermostability, and using the temperature of the screening assay as selection pressure [34 - 36]. This could for instance include development of thermostable cellobiohydrolases, which are uncommon among thermophiles
	Published journal article available from PubMed Central
	<u>similar results</u>
□ 3.	Bibliography Carbohydrate Polymers, 62 (2), p.199-204, Nov 2005characterization of plasticized cellulose acetate biocomposite with natural fiber CzajaBiotransform 2004 22 (5-6) 383 Influence of steam and dry heat pretreatment on fibre properties57 (3-4) 124 Impact of high hydrostatic pressure treatment on the resistant starch content
	Published journal article available from ScienceDirect
	view all 6 results from ScienceDirect similar results
4.	Pretreatment of Miscanthus for hydrogen production by Thermotoga elfii de Vrije, T. / de Haas, G.G. / Tan, G.B. / Keijsers, E.R.P. / Claassen, P.A.M. , International Journal of Hydrogen Energy, 27 (11), p.1381-1390, Nov 2002treated with NaOH during or following extrusion (samples E2-E4) showed a
	comparable3). Fig. 3 Enzymatic hydrolysis of extruded and NaOH-pretreated Miscanthus . () E1 () , E2 () E3 and () E4. () extruded and steam pretreated Miscanthus . Enzyme activities
	Published journal article available from ScienceDirect
	view all 6 results from ScienceDirect similar results
□ 5.	Bibliography of carbohydrate polymers Carbohydrate Polymers, 32 (3), p.321-326, Mar 1997

...diffusion of water and al- cohols in cellulose acetate Pron A, Nicolau Y, Genoud F, Nechtschein...transparent, and conduct polyaniline-cellulose acetate composite films Rakhmanberdyev GR, Fedyakova...Appl Chem 1997 A34 (1) 153 Sugar cane bagasse lignin in resol-type resin: Alternative... Published journal article available from ScienceDirect view all 6 results from ScienceDirect similar results **6.** Composites reinforced with cellulose based fibres Bledzki, A.K. / Gassan, J., Progress in Polymer Science, 24 (2), p.221-274, May 1999 ...technology (e.g. microbial deterioration, steam explosion) used is one of the essential...tensile explosion process and the new steam explosion process, that is, the **pressure** process [8,9] . In this new **steam** explosion...**steam**, and additives if necessary, under pressure and with increased temperature, penetrate... Published journal article available from Science Direct view all 6 results from ScienceDirect similar results **7.** Bibliography on carbohydrate polymers Carbohydrate Polymers, 10 (3), p.230-253, Jan 1989 ...structure (Blanshard JMV) Extrusion and co-extrusion of cereals...gas mixtures in cellulose acetate membranes - practical approach...of cellulose and cellulose acetate Studies on gas transport through dry cellulose acetate membranes prepared by solvent...29 (5) 462 Comparison of steam and ammonia pretreat- ment... Published journal article available from ScienceDirect view all 6 results from ScienceDirect

similar results



Post Your CV & Get Results

About Us

Newsroom

Advisory Board

Submit Web Site

Help

Contact Us

Basic Search

Advanced Search Preferences

		"cellulose aceta	te" AND manufacturing	AND steam ANI	Search	
		☑ Journal sources	Preferred Web sources	Other Web sources	Exact phrase	
Saar	ched for::	· All of the words:"	collulace acetate" AND m	anufacturing AND sto	am AND town out to	
Seai			cellulose acetate" AND m	_	•	AN
	Found::	:168 total <u>3 jou</u>	rnal results 147 prefer	red web results 18 o	ther web results	
	Sort by::	:relevance <u>date</u>	L			
1.	Process fo		Email checked results cellulose molding, plant	Export checked resul		Dic <u>"C€</u> <u>m</u> a
	Matsuo, S	Shunichi / Taka ION, Sep 2004	mura, Takatsugu (Ce	ljan Co. Ltd.), <i>EUROI</i>	PEAN PATENT	ter (k€ ke
	provide manufact and a pre 350°Cfo Full text	a process for ma turing a cellulose ssure of 20 to 29 or a process for m available at pat 47 results from Pa	nufacturing cellulose moldingcorncob med MPasub-critical water anufacturing cellulose ent office. For more in the more i	al at a temperature er having a tempera se acetate, the proc	of 150 to 250°C ature of 300 to cess comprising	Re us for ace ace ace cel
2.	process fo Matsuo, S TRADEMAI patno: US 2	r producing cellul Shunichi / Taka R <i>K OFFICE PRE-G</i> 20040241302	mura, Takatsugu , <i>UN</i> <i>GRANT PUBLICATION</i> , D	ITED STATES PATEN ec 2004	T AND	pro cel cel eth
	dehydratic cana ha acetate o Full text	on0085] The cerdening temperare f the presentm available at pate from Pare from	5 to 15 MPa10 MPa. ellulose acetate obtain ture, can be carried anufacturing cellulos ent office. For more intent Offices	ned byabove direct process for manuface se acetate according	pressure molding cturing cellulose to	fibi filti gly pla pla pol
3.	May 2007sourcing Chillersr measurem Cellulose [http://che	measurement & comment & commentWord Count Acetate Industremindustry.com/p from [http://che	acturing / synthesisr ontrol Pressure measu t: cellulose acetate (5 ial Chemicals: Cellulos popular/C/cellulose_ace mindustry.com]	rementinstrument 5691) FindIndustria e Acetate Industria	team equipment is Temperature al Chemicals:	Or Al

4. GRSDC RESEARCII PRC) GRILM14E [PDF-79K] Aug 2001 ...tion, filter pressure drop and blend...which includes cellulose acetate (control), polypropylene...the tube into cellulose acetate filters by spin...foam, preferably cellulose acetate,.or polypropylene...tively high pressure drop is generated...evaluate the filter manufacturing process (spin... [http://www.hlth.gov.bc.ca/guildford/pdf/083/00008426.p...] more hits from [http://www.hlth.gov.bc.ca] similar results **5.** No Title [9K] Jun 2005 ...differential pressure (25°C) 4.0 kg...Max. operating temperature 80°C (176° F...Prefilter membrane Cellulose acetate Final membrane...differential pressure (25°C) 5.0 kg...Max. operating temperature 80°C (176°F...Membrane Coated cellulose acetate Core tube Polypropylene...Polypropylene Coated Cellulose Acetate (single [http://www.clarksonlab.com/micf/PDF/capsules.pdf] more hits from [http://www.clarksonlab.com] similar results 6. CELLULOSE ACETATE AND PROCESS FOR PRODUCING THE SAME OZAKI, Toru / SASAI, Hirofumi / TANIGUCHI, Hiroki / NAKAI, Michiyo / SUZUKI, Shinsuke (DAICEL CHEMICAL INDUSTRIES, LTD.), EUROPEAN PATENT APPLICATION, Jan 2003 patno: EP1270597 ...from a dope of cellulose acetate, an excessively...desirable to provide cellulose acetate having a small...improvement of the manufacturing process, in...technique of a high-temperature acetylation...clogging constant Cellulose acetate is dissolved...under a constant pressure at the filtration...2)) and the temperature of 25° C using... Full text available at patent office. For more in-depth searching go to CiexisNexis. view all 147 results from Patent Offices similar results 7. Statement of Legal and Factual Basis [22K] Apr 2005 ...Permit for its cellulose acetate flake and fiber manufacturing facility located...Cellulose Acetate Manufacturing. In cellulose acetate manufacturing...recycled from cellulose acetate manufacturing and ketene anhydride... [http://www.deq.state.va.us/air/pdf/titlevpermits/20304...] similar results **8.** No Title [ASCII-9K] Dec 2006 ...the course of manufacturing for the purpose...and cocoa. 19. CELLULOSE ACETATE It fibrous form...collection of cellulose acetate fibre& (tow...gloving high temperature (800 - 9W'C...increasing the PRESSURE DRO? (q.v.) obtained...name (LASTW) for cellulose acetate filter tow. 41...flue-cured). The nano steam from the laboratory... [http://www.library.ucsf.edu/tobacco/batco/OCR/16600/16...] similar results **9.** Process of manufacturing cellulose acetate SULZER ALBERT F, UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Nov. 1925 patno: US1560620 ...process of manufacturing cellulose acetate, the steps...vacuum, a cellulose

acetate reaction...values at a temperature below the one at which the cellulose

acetate is degraded...maintaining the pressure thereof below... Full text available at patent office. For more in-depth searching go to LexisNexis view all 147 results from Patent Offices similar results 10. AY-1A ESTRON and CHROMSPUN Acetate Yarn [11K] Mar 2007 ...of heat and pressure. As a result...production of cellulose acetate for use as...we provided cellulose acetate to the United...acetate yarn manufacturing. • 2005...flake called cellulose acetate. Spinning The... [http://www.eastman.com/NR/rdonlyres/146A7047-9A4F-4593...] similar results 11. Cellulose acetate and process for producing the same Ozaki, Toru / Sasai, Hirofumi / Taniguchi, Hiroki / Nakai, Michiyo / Suzuki, Shinsuke, UNITED STATES PATENT AND TRADEMARK OFFICE PRE-GRANT PUBLICATION. May 2003 patno: US20030092906 ... superheated **steam** into the system and adjusting **temperature** and time. Subsequently...give a flaky cellulose acetate. (Example 4...superheated steam into the system and adjusting temperature and time. Subsequently...give a flaky cellulose acetate. (Example 7...superheated steam into the system and adjusting temperature and time. Subsequently...give a flaky cellulose acetate. 1TABLE ${\tt 1Comparative Example Example 123456712 Acetylation}...$ Full text available at patent office. For more in-depth searching go to LexisNexisview all 147 results from Patent Offices similar results 12. CIGARETTES AND FILTER SUBASSEMBLIES WITH SQEEZABLE FLAVOR CAPSULE AND METHODS OF MANUFACTURE KARLES, Georgios D. / ALLEN, Jeffrey / NEPOMUCENO, Jose (PHILIP MORRIS PRODUCTS S.A.), PATENT COOPERATION TREATY APPLICATION, Nov 2006 patno: WO06117697 ...methods of manufacturing cigarettes...comprised of cellulose acetate and the second...comprised of cellulose acetate. In another...preferably steam set, A third...method for manufacturing cigarette...layer of cellulose acetate is steam... Full text available at patent office. For more in-depth searching go to LexisNexisview all 147 results from Patent Offices similar results 13. Process for extruding plasticized open cell foamed cellulose acetate filters Howell, Carl J. / Trott, David W. / Riley, Jesse L. (Celanese Corporation), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Dec 1979 patno: US4180536 ...to a method of manufacturing foamed cellulose acetate and the product...inert gas under pressure into ripened...sulfate content of cellulose acetate should be controlled...and elevated temperature viscosities...hydrochloric acid in a steam autoclave to...content of the cellulose acetate flake employed... Full text available at patent office. For more in-depth searching go to LexisNexisview all 147 results from Patent Offices similar results 14. Intermediate product in the manufacture of cellulose acetate SEEL PAUL C, UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, May 1925 patno:US1536311 ...stored at room temperature and pressure, so that when...in the final cellulose acetate product. Other...for process of manufacturing cellulose acetate. As a

result...of-which comprised cellulose acetate mixed with acetic...

Full text available at patent office. For more in-depth searching go to CexisNexis* view all 147 results from Patent Offices similar results ☐ 15. Process for the production of nonwoven cellulose acetate laminate cured with phenolic Arisaka, Katsuharu / Sawada, Hideo / Shimoguchi, Kozo (Daicel, Ltd.), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT. Feb 1977 patno: US4008301 ...superheated steam at a pressure of from 0.05...sup.2 and a temperature of from 80.degree...removing the cured cellulose acetate fiber web from...wherein said cellulose acetate fibers have...superheated steam at a pressure of from 0.05...sup.2 and a temperature of from 80.degree...removing the cured cellulose acetate fiber web Full text available at patent office. For more in-depth searching go to LexisNexis. view all 147 results from Patent Offices similar results **16.** Open cell structure foamed cellulose acetate filters Howell, Carl J. / Trott, David W. / Riley, Jesse L. (Celanese Corporation), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Aug 1981 patno:US4282890 ...maintained at a temperature of from -20.degree...extruder is a high pressure, high shear zone...temperature of cellulose acetate. The third zone...sulfate content of cellulose acetate should be controlled...and elevated temperature viscosities...hydrochloric acid in a steam autoclave to...content of the cellulose acetate flake employed... Full text available at patent office. For more in-depth searching go to **LexisNexis** view all 147 results from Patent Offices similar results **17.** Chemical Industries NewsletterJuly 2006 [27K] Dec 2006 ...is captive by producers of cellulose acetate and related products. Much...recovered acetic acid from cellulose acetate operations. In Europe, most...anhydride is consumed in **cellulose acetate** production tetraacetylethylenediamine... [http://ecom.sric.sri.com/nl/Public/2006Dec.pdf] similar results **18.** Process for making fibrillated cellulose acetate staple fibers Frederick, Tim J. / Mitchell, Melvin G. / Partin, Lee R. / Wilson, Alan K. / Neal, Richard D. (Eastman Chemical Company), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Jul 1998 patno: US5779736 ...of the squeeze pressure. The water take-up...water per lb of cellulose acetate. The base application...operated at various temperatures from the solution...1 One bale of cellulose acetate filter tow of...C. and sparge steam on the tow. The...proceeded at room temperature (approximately...EXAMPLE 2 Six cellulose acetate filter tow bands... Full text available at patent office. For more in-depth searching go to LexisNexisview all 147 results from Patent Offices similar results **19.** Process for preparation of cellulose acetate Ikemoto, Yoshiyuki (Daicel Chemical Industries, Ltd.), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Dec 1981 patno: US4306060 ...of a primary cellulose acetate containing a...however, because steam is directly introduced...out at a high temperature and a stirring...autoclave and steam was

introduced...under a gauge **pressure** of 5 Kg/cm.sup.2. After the **temperature** was elevated...the thus-formed **cellulose** acetate. The precipitate...thus-obtained **cellulose** acetate flakes were characterized...

Full text available at patent office. For more in-depth searching go to view all 147 results from Patent Offices similar results

20. CELLULOSE ACETATE AND STARCH BASED BIODEGRADABLE INJECTION MOLDED PLASTICS COMPOSITIONS AND METHODS OF MANUFACTURE

MAYER, Jean M. / ELION, Glenn R. (THE UNITED STATES OF AMERICA, represented by THE SECRETARY OF THE ARMY), PATENT COOPERATION TREATY APPLICATION, Jan 1995

patno: WO9501395

...formed under high **temperature** and **pressure** into gelatinized...or at elevated **temperatures**, rendering them...plasticizer used with **cellulose acetate** was triacetin...needed to makes **cellulose acetate** based plastics...

Full text available at patent office. For more in-depth searching go to view all 147 results from Patent Offices similar results

##fast

Results Pages: [<< Prev] 1 <u>2 3 4 5 6 7 8 9 [Next >>]</u>

back to top

"cellulose acetate" AND manufacturing AND steam ANI

Search

☑ Journal sources ☑ Preferred Web sources ☑ Other Web sources ☑ Exact phrase

<u>Downloads</u> | <u>Library Partners</u> | <u>Subscribe to News Updates</u> | <u>User Feedback</u> <u>Advertising</u> | <u>Tell A Friend</u> | <u>Terms Of Service</u> | <u>Privacy Policy</u> | <u>Legal</u>

Powered by FAST © Elsevier 2007





About Us Newsroom Advisory Board

Submit Web Site

Help

Contact Us

Basic Search

Advanced Search Preferences

	"cellulose acetate" AND manufacturing AND steam ANI Search	
	Journal sources Preferred Web sources Other Web sources Exact phrase	
Sea	rched for:: :All of the words:"cellulose acetate" AND manufacturing AND steam AND temperature	AN
	Found:: :16 total 0 journal results 15 preferred web results 1 other web results	
	Sort by:: :relevance date	
	Save checked results Email checked results Export checked results	Dic
1 .	Process for manufacturing cellulose molding, plant component extracting apparatus, and process for producing cellulose acetate	<u>"се</u> <u>т</u> а
	Matsuo, Shunichi / Takamura, Takatsugu (Celjan Co. Ltd.), EUROPEAN PATENT	ter (ke
	APPLICATION, Sep 2004 patno: EP1462238	key (bi
	process for manufacturing celluloseby using bagasse, kenaf, reeds or rice straw	<u>re</u> e
	asprocess for manufacturing a cellulosemeal at a temperature of 150 to 250°C and a pressure of 20 tohaving a temperature of 300 toprocess for manufacturing	Re
	cellulose acetate, the processselected from bagasse, kenaf, reeds and rice straw	us foi
	in Full text available at patent office. For more in-depth searching go to CLexisNexis.	<u>tri</u> ;
	view all 15 results from Patent Offices	Or
	similar results	Al
2	Process for manufacturing cellulose molding, plant component extracting apparatus, and process for producing cellulose acetate	
	Matsuo, Shunichi / Takamura, Takatsugu, UNITED STATES PATENT AND	F
	TRADEMARK OFFICE PRE-GRANT PUBLICATION, Dec 2004 patno:US20040241302	
	out under a pressure of 5 to 15 MPa10 MPa. The temperature for the	
	dehydration0085] The cellulose acetate obtained byabove direct pressure molding cana hardening temperature , can be carriedprocess for manufacturing cellulose	
	acetate of the presentmanufacturing cellulose acetate according to	
	Full text available at patent office. For more in-depth searching go to LexisNexis- view all 15 results from Patent Offices	
	similar results	
<u> </u>	CELLULOSE ACETATE AND STARCH BASED BIODEGRADABLE INJECTION MOLDED	
	PLASTICS COMPOSITIONS AND METHODS OF MANUFACTURE MAYER, Jean M. / ELION, Glenn R. (THE UNITED STATES OF AMERICA, represented	٠
	by THE SECRETARY OF THE ARMY), PATENT COOPERATION TREATY APPLICATION, Jan 1995	
	patno: WO9501395	
	Reaction temperatures usually are350C. For cellulose acetate synthesestemperature and pressure into gelatinized used with cellulose acetate	

was triacetin...method of manufacturing is needed to makes cellulose acetate based plastics... Full text available at patent office. For more in-depth searching go to LexisNexis view all 15 results from Patent Offices similar results **4.** Cellulose acetate and starch based biodegradable injection molded plastics compositions and methods of manufacture Mayer, Jean M. / Elion, Glenn R. (The United States of America as represented by the Secretary of the Army), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Feb 1994 patno: US5288318 ...Reaction temperatures usually are...under high temperature and pressure into gelatinized...at elevated temperatures, rendering...method of manufacturing is needed...sorghum, rice and arrowroot...amylose. The cellulose acetate in the present...30% to 70% cellulose acetate which has... Full text available at patent office. For more in-depth searching go to LexisNexisview all 15 results from Patent Offices similar results **5.** Process for making fibrillated cellulose acetate staple fibers Frederick, Tim J. / Mitchell, Melvin G. / Partin, Lee R. / Wilson, Alan K. / Neal, Richard D. (Eastman Chemical Company), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Jul 1998 patno: US5779736 ...removal from the **cellulose acetate** for a target application...weight loss in the cellulose acetate. To prevent Tinting...of the squeeze pressure. The water takeup...water per lb of cellulose acetate. The base application...operated at various temperatures from the solution...atmospheric sparge steam in a steam tube... Full text available at patent office. For more in-depth searching go to ClexisNexisview all 15 results from Patent Offices similar results **6.** No Title [158K] Mar 2003 ...resulting rise in temperature. Mathematically...substance is cellulose acetate (FTC definition...resultant product, cellulose acetate flake, is precipitated...treated with a cellulose acetate dope and used...place by air pressure. ALBATROSS... [http://www.celanese.com/textile_glossary_filament_acet...] similar results 7. MEANS FOR MANUFACTURING STAPLE FIBER FILTER ELEMENTS BERGER RICHARD M / SPROULL REAVIS C (AMERICAN FILTRONA CORPORATION). UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Apr 1972 patno:US3658626 ...of plasticized cellulose acetate plication Ser...physical and ""der Pressure against the tow...layer to form manufacturing methods in most...disperses the steam-treating station...while the <HR>steam serves to efficiently...In fact, the steam 188 into the funnel...terminology the cellulose acetate tow is generally...including shredded bagasse fibers, cotton... Full text available at patent office. For more in-depth searching go to LexisNexisview all 15 results from Patent Offices similar results

8. Filtration materials

Beven, John Lawson / Case, Paul David / Coleman, Martin / Greig, Colin Campbell / White, Peter Rex (British-American Tobacco Company Limited), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Sep 1999 patno: US5954059

...operating temperature of the extrusion...operating pressure, wherein...consisting of cellulose acetate, polypropylene...example, cellulose acetate. The material...process. If **cellulose acetate** is used...Company. **Rice** or tapioca... Full text available at patent office. For more in-depth searching go to **LexisNexis** view all 15 results from Patent Offices similar results **9.** Extruded filtration materials Beven, John Lawson / Case, Paul David / Coleman, Martin / Greig, Colin Campbell / White, Peter Rex (British American Tobacco (Investments) Limited), EUROPEAN PATENT, Sep 1994 patno: EP614620 ...such heat and pressure conditions...elements of cellulose acetate and paper were...controlled elevated temperatures. The conditions...vaporisation to steam of at least...consisting of cellulose acetate, polypropylene...for example, cellulose acetate. The material...Chemical Company. **Rice** or tapioca... Full text available at patent office. For more in-depth searching go to LexisNexisview all 15 results from Patent Offices similar results ☐ 10. SELECTIVE FILTRATION DEVICE DOUGLAS, Annmarie, Veronica / GEER, Robert, Gillette / MORGAN, Benji, Dawn (KIMBERLY-CLARK CORPORATION), PATENT COOPERATION TREATY APPLICATION, Feb. 1996 .patno:WO9605744 ...high-speed manufacturing processes...tobacco and bagasse. As used...conventional cellulose acetate filter" refers...filter made of cellulose acetate tow treated...conventional cellulose acetate filter for...process. Steam can or steam... Full text available at patent office. For more in-depth searching go to **LexisNexis** view all 15 results from Patent Offices similar results **11.** Selective filtration device Douglas, Annmarie Veronica / Geer, Robert Gillette / Morgan, Benji Dawn (Schweitzer-Mauduit International, Inc.), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Mar 1998 patno: US5732718 ...web may be non-compressibly dried utilizing a conventional steam can or steam roll arrangement shown in FIG. 1 at 34. The wet-formed adsorbent...composite material 28 passes over drums 36-42 heated to a temperature ranging from about 150.degree.-175.degree. F. (65.degree... Full text available at patent office. For more in-depth searching go to LexisNexisview all 15 results from Patent Offices similar results 12. SELECTIVE FILTRATION DEVICE DOUGLAS, Annmarie, Veronica / GEER, Robert, Gillette / MORGAN, Benji, Dawn (Schweitzer-Mauduit International, Inc.), EUROPEAN PATENT, Jul 1997 patno: EP782400 ...high-speed manufacturing processes...tobacco and bagasse. As used...conventional cellulose acetate filter" refers...filter made of cellulose acetate tow treated...conventional cellulose acetate filter for...process. Steam can or steam... Full text available at patent office. For more in-depth searching go to LexisNexisview all 15 results from Patent Offices similar results 13. FILTER PLUG OF STAPLE FIBER FILTER ELEMENTS AND THE LIKE SPROULL REAVIS C / BERGER RICHARD M (AMERICAN FILTRONA CORPORATION). UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Jan 1971

patno: US3552400

...station. The bore of the **steam**-treating sta- **steam** serves to efficiently...moisture. In fact, the **steam**: 188 into the funnel...the terminology the **cellulose acetate** tow is generally sufficient...including shredded **bagasse** fibers, cotton linters...

Full text available at patent office. For more in-depth searching go to <u>view all 15 results from Patent Offices</u>
similar results

Fibrous web having improved strength and method of making the same Halabisky, Donald D. / West, Hugh / Hajnal, Andre S. / Grant, Terry M. (Weyerhaeuser Company), UNITED STATES PATENT AND TRADEMARK OFFICE GRANTED PATENT, Nov 1998 patno:US5837627

...Straw, flax, kenaf or similar...the fibers to steam, or chemical...Fiber Sheet

Manufacturing With Reactivatable...has a vapor pressure of 29 kPa or...cellulose
acetate triacetin propane...mediums listed, cellulose acetate is the most...manufacture
of cellulose acetate fibers, a finish...

Full text available at patent office. For more in-depth searching go to view all 15 results from Patent Offices similar results

**I 15. FIBROUS WEB HAVING IMPROVED STRENGTH AND METHOD OF MAKING THE SAME HALABISKY, Donald D. / WEST, Hugh / HAJNAL, Andre S. / GRANT, Terry M. (WEYERHAEUSER COMPANY; HALABISKY, Donald, D.; WEST, Hugh; HAJNAL, Andre, S.; GRANT, Terry, M.), PATENT COOPERATION TREATY APPLICATION, Sep 1996 patno: WO9627703

...with accurate **temperature** control systems...as straw, **kenaf** or similar...photomicrograph of **cellulose acetate** fibers and...photomicrograph showing **cellulose acetate** fibers bonded...photomicrograph showing **cellulose acetate** fibers bonded...fibers to **steam**, or chemical...Fiber Sheet **Manufacturing** With Reactivatable...has a vapor **pressure** of 29 kPa...

Full text available at patent office. For more in-depth searching go to view all 15 results from Patent Offices similar results

16. Improvements in or relating to the manufacture of laminated glass (LOUIS BARTELSTONE), UNITED KINGDOM PATENT APPLICATION, Nov 1927 patno:GB0279671

...encountered in **manufacturing** such a product...all and IP **rice** 1 /-I in which...glass under a **pressure** exceeding...time and the **temperature** being in the...that of a **steam** table) and...sheets of **cellulose acetate** may be employed...inasmuch as **cellulose acetate** can be obtained...celluloid or **cellulose acetate** is 130 279...

Full text available at patent office. For more in-depth searching go to view all 15 results from Patent Offices similar results

Sponsored links

<u>Cellulose Manufacturers</u>
Alibaba B2B online marketplace. Forbes Magazine Best of the Web.
www.Alibaba.com

:::fast

"cellulose acetate" AND manufacturing AND steam ANI

Search

☑ Journal sources ☑ Preferred Web sources ☑ Other Web sources ☑ Exact phrase

<u>Downloads</u> | <u>Library Partners</u> | <u>Subscribe to News Updates</u> | <u>User Feedback</u> <u>Advertising</u> | <u>Tell A Friend</u> | <u>Terms Of Service</u> | <u>Privacy Policy</u> | <u>Legal</u>

Powered by FAST © Elsevier 2007

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S2	3	((SHUNICHI) near2 (MATSUO)). INV.	US-PGPUB; USPAT	NEAR	ON	2007/08/22 09:45
S3	21	((SHUNICHI) near2 (MATSUO)). INV.	EPO; JPO; DERWENT	NEAR	ON	2007/08/21 14:43
S4	5	((TAKATSUGU) near2 (TAKAMURA)).INV.	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:56
S5	4	((TAKATSUGU) near2 (TAKAMURA)).INV.	EPO; JPO; DERWENT	NEAR	ON	2007/08/21 14:43
S6	8	("1522618" "4306060" "4520105" "5371207" "5658765" "6228213" "6352644").PN. OR ("6984731").URPN.	US-PGPUB; USPAT; USOCR	NEAR	ON	2007/08/21 14:45
S 7	94590	bagasse or kenaf or reeds	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:56
S8	66399	cellulose acetate	US-PGPUB; USPAT	NEAR	ON ⁻	2007/08/21 15:35
S9	1588	S7 and S8	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:56
S10	65606	cellulose adj acetate	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:59
S13	1577	S10 and S7	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:57
S14	354	S13 and steam	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:58
S15	330	S14 and pressure	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:58
S16	211	S15 and filter\$	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:58
S17	3	S16 and (acetic anhydride)	US-PGPUB; USPAT	NEAR	ON	2007/08/21 14:59
S18	7340	(cellulose adj acetate).clm.	US-PGPUB; USPAT	NEAR	ON ·	2007/08/21 15:00
S19	7340	(cellulose adj acetate).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:25
S20	184	S19 and S7	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:25

S21	39	S20 and steam	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:25
S22	22	S21 and (filter or filtering)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:34
S23	21	S22 and pressure	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:30
S24	. 79	"5288318"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:30
S25	2	"5288318".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:33
S26	18121	sugar cane	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:35
S27	39	S26 and S19	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON .	2007/08/21 15:34
S28	16	S27 and (filter or filtering)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:34

		· · · · · · · · · · · · · · · · · · ·	_	r	1	
S29	799	sugar cane bagasse	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON .	2007/08/21 15:35
S30	21	S29 and S10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR .	ON	2007/08/21 15:35
S31	27	S29 and (cellulose acetate)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:40
S33	2	"7097738"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/21 15:40
S34	1	"6228213".pn.	US-PGPUB; USPAT	NEAR	ON	2007/08/21 16:05
S35	1	"5371207".pn.	US-PGPUB; USPAT	NEAR	ON .	2007/08/22 08:37
S36	2	"5371207".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/22 08:48
S37	2	"5244945".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/22 08:48
S38		("20040241302" "5358725" "3982032" "4243689" "5534273" "5578338" "6680076" "20030086983" "20040022927" "20060165869" "3741715" "3784389" "3799735" "3864075" "3881024" "3932116" "3938949" "3982886" "4002420" "4004876"). pn.	US-PGPUB; USPAT	NEAR	ON	2007/08/22 09:46

			т			Ţ····
S39	56	(("(20040241302") or ("5358725") or ("3982032") or ("4243689") or ("5534273") or ("5578338") or ("6680076") or ("20030086983") or ("20040022927") or ("20060165869") or ("3741715") or ("3784389") or ("3799735") or ("3864075") or ("3881024") or ("3932116") or ("3938949") or ("3982886") or ("4002420") or ("4004876") or (").pn.")).PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/08/22 11:10
S40	2	("6228213").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/08/22 11:38
S41	17	bagasse NEAR10 cellulose NEAR10 crush\$	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/22 11:42
S42	1	bagasse NEAR10 cellulose NEAR10 extrud\$	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/22 11:55
S43	19	("1522618" "4306060" "4520105" " 5371207" "5658765" "6228213" "63 52844").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON .	2007/08/22 11:45
S44	. 2	bagasse NEAR10 cellulose NEAR10 (knead\$ or steaming)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON	2007/08/22 11:57
S45	13	(bagasse or kenaf or reeds or rice) NEAR10 cellulose NEAR10 (knead\$ or steaming)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	NEAR	ON .	2007/08/22 11:58